SAFETY DATA SHEET

Revision Date: 12/30/14

This Safety Data Sheet may be used to comply with OSHA's Hazard Communication Standard, 29 CFR 910.1200 and ANSI Z400-1-1998.

Section 1: Identification of the Product and of the Company

Product Code GC-001
Trade Name GC-001
Speedy White

Product Description Hearth & Stove Cleaner

Manufacturer Plesh Contract Packaging Address 711 Northland Avenue

Buffalo, NY 14211

Phone (716) 883-4000 (8am-4pm M-F)

Fax (716) 892-1171

Chemtrec (800) 262-8200 (24 hour)

Outside U.S. (703) 741-5500

Section 2: Hazards Identification

OSHA Hazards Irritant

Signal Word Warning

Hazard Statement(s) H302 Harmful if swallowed

H315 Causes skin irritation H320 Causes eye irritation

Pictogram(s)



Precautionary Statement(s) P305 IF IN EYES: Rinse cautiously with water for several minutes.

+351 Remove contacts if present and easy to do so -

+338 continue rinsing.

Section 3: Composition/Information on Ingredients

Hazardous Component CAS (OSHA 29 CFR 1910.1200)

Sodium Hydroxide 1310-73-2 Ethylene Glycol Monobutyl Ether 111-76-2

The specific chemical identities and/or exact percentage concentration of composition may have been withheld as a trade secret.

VOC Compliant 3/10/05

Section 4: First Aid Measures

Inhalation None known

Skin Contact Wash with soap and water. Rinse thoroughly.

Eye Contact Rinse with water for 15 minutes. Get medical attention if irritation persists.

Ingestion Do not induce vomiting. Obtain medical attention.

Symptoms/Effects None known.

Section 5: Firefighting Measures

Hazardous Combustion Products Possiblity of hydrogen gas if exposed to aluminum.

Firefighting Instructions Use water mist to cool fire exposed drum.

Firefighting Equipment Bunker gear and SCBA.

Section 6: Accidental Release Measures

Land Spill Avoid run off into storm sewers or ditches by containment with sand or

absorbent materials.

Water Spill Remove from water with suitable absorbent materials.

Section 7: Handling and Storage

Precautions for Safe Handling Take normal care to prevent prolonged skin contact.

Precautions for Safe Storage Keep from freezing or heating above 110°F. Store in original container.

Section 8: Exposure Controls/Personal Protection

Components OSHA PEL & ACGIH TLV

Sodium Hydroxide 2 mg/m^3 Ethylene Glycol Monobutyl Ether 50ppm, 20ppm

Mechanical ventilation is not needed under normal conditions. **Engineering Controls**

Personal Protective Measures Wear eve and hand protection.

Section 9: Physical and Chemical Properties

Non-viscous, clear blue liquid **Boiling Point** Not available Appearance Odor Glycol Ether Solubility in Water Completely Odor Threshold Not available Percent Volatile Not available Vapor Pressure Not available Flash Point and Method Will not flash Vapor Density Not available Flammable Limits Not available Specific Gravity 1.0 @ 70°F Auto Ignition Temperature Not available **Decomposition Temperature** Hq 12.4-13.7 Not available **Evaporation Rate** Viscosity Not available <1 (n-butyl acetone=1) Weight/Gallon Partition Coefficient: n-octanol/water Not available 8.40 lb/gal Freezing Point 29 g/liter (calculated)

VOC%

Not available

Section 10: Stability and Reactivity

Chemical Stability This product is stable and hazardous polymerization will not occur.

Materials to Avoid Metals and strong acids.

Conditions to Avoid None known.

Hazardous Decomposition Possibility of hydrogen gas if exposed to aluminum.

Section 11: Toxicological Information

The complete toxicological data for each ingredient is unknown & otherwise beyond the scope of this document.

Section 12: Ecological Information

Product is harmful to fish and algae upon immediate exposure.

Section 13: Disposal Considerations

Refer to Sections 5, 6, and 15 for additional disposal and regulatory information.

Section 14: Transportation Information

DOT Shipping Description Unrestricted/Non-regulated.

Section 15: Regulatory Information

TSCA All components are listed on the TSCA.

CERCLA Not reportable

SARA Title III No known reportable ingredients.

Section 16: Other Information

NFPA Rating Health Hazard-1 Fire-0 Reactivity Hazard-0

Key: 4=severe, 3=serious, 2=moderate, 1=slight, 0=minimal

Disclaimer The information contained herein is based on data considered accurate.

However, no warranty is expressed or implied regarding the accuracy of

this data or the results to be obtained from the use thereof.

Vendor assumes no responsibility for injury to vendee or third person. Proximate cause by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material, even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his

use of the material.